

## Material Safety Data Sheet

Material Name: Hexafluoroethane

MSDS ID: Hynote-0026

### Section 1- Product and Company Identification

Synonyms: Freon ®116, Halocarbon 116, perfluoroethane

Chemical Name: Hexafluoroethane

Formula: C<sub>2</sub>F<sub>6</sub>

TDG (Canada) CLASSIFICATION: 2.2

WHMIS CLASSIFICATION: A, D2B

ShangHai Hynote

906#, Tower A, Tomson Center,

228 ZhangYang Road, PuDong,

ShangHai, PRC.

EMERGENCY Telephone Numbers:

+86-21-58790001 (In South China):

+86-379-65867058 (In North China)

+86-10-110/119/120 (24 Hours)

Product Information: +86-379-65867058

MSDS Information Email: hynote@shtel.net.cn

### Section 2- Composition/information on ingredients

COMPOSITION: 99.9 %

PEL-OSHA<sup>1</sup>: None Available

CAS NUMBER: 76-16-4

TLV-ACGIH<sup>2</sup>: None Available

RTECS #: KI4110000

LD<sub>50</sub> or LC<sub>50</sub> Route/Species: LC<sub>50</sub>>200,000 ppm/2hr (rat)

Formula: C<sub>2</sub>F<sub>6</sub>

<sup>1</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993).

<sup>2</sup> As stated in the ACGIH 1994-95 Threshold Limit Values for Chemical Substances and Physical Agents.

### Section 3- Hazards Identification

#### EMERGENCY OVERVIEW

This product does not contain oxygen and may cause asphyxia if released in a confined area.

Fluorocarbons can cause irritation, central nervous system depression and irregular heart beat at high concentrations. Nonflammable but decomposes to toxic gases, including hydrofluoric acid, under fire conditions.

**ROUTE OF ENTRY:**

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	No

**HEALTH EFFECTS:**

Exposure Limits Yes	Irritant Yes	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None Reported		

**Carcinogenicity:**

NTP: No      IARC: No      OSHA: No

**EYE EFFECTS:**

PERSONS WITH POTENTIAL EXPOSURE SHOULD NOT WEAR CONTACT LENSES.

**SKIN EFFECTS:**

None anticipated as product is a gas at room temperature.

**INGESTION EFFECTS:**

Ingestion is not likely.

**INHALATION EFFECTS:**

Product is relatively nontoxic. Fluorocarbons can irritate the eyes, mucous membranes and respiratory system.

Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or vomiting leading to unconsciousness. At high concentrations narcotic effects may be produced and may cause the heart to beat irregularly and stop.

Oxygen deficiency may occur in the presence of high concentrations resulting in asphyxiation.

Maintain oxygen levels above 19.5% at sea level.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Pre-existing heart condition.

**NFPA HAZARD CODES**

Health: 1

Flammability: 0

Reactivity: 0

**HMIS HAZARD CODES**

Health: 1

Flammability: 0

Reactivity: 0

**RATINGS SYSTEM**

0 = No Hazard

1 = Slight Hazard

2 = Moderate Hazard

3 = Serious Hazard

4 = Severe Hazard

Section 4- First Aid Measures
-------------------------------

**EYES:**

Never introduce ointment or oil into the eyes without medical advice! If pain is present, refer the victim to an ophthalmologist for treatment and follow up.

**SKIN:**

Remove contaminated clothing and flush affected areas with lukewarm water. If irritation persists, seek medical attention.

**INGESTION:**

Unlikely as product is a gas at room temperature.

**INHALATION:**

**PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE.**

**RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.** Remove victim to fresh air. Administer artificial respiration if breathing has stopped and supplement with oxygen by a trained individual. Further treatment should be symptomatic and supportive. Seek medical attention as soon as possible for follow up treatment. Remove to fresh air. If necessary, give oxygen or provide artificial respiration. Call a physician.

**NOTE TO PHYSICIAN:** A patient adversely affected by exposure to this product should not be given adrenalin (epinephrine) or similar heart stimulant since these would increase the risk of cardiac arrhythmias.

Section 5- Fire-Fighting Measures
-----------------------------------

Conditions of Flammability: Nonflammable		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None	UEL(%): None	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

**FIRE AND EXPLOSION HAZARDS:**

If involved in a fire, product may decompose yielding toxic products, which may include hydrofluoric acid and carbonyl fluoride.

**EXTINGUISHING MEDIA:**

None required. Use media appropriate for surrounding flammable substances.

**FIRE FIGHTING INSTRUCTIONS:**

Positive-pressure, self-contained respiratory equipment for fires involving large quantities of this material.

Section 6- Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or containervalue, contact the appropriate emergency telephone number listed in Section 1 or call your closest Hynote location.

Section 7- Handling and Storage

Product is noncorrosive and may be used with any common structural material. Silver and carbon bearing alloys can act as catalysts for decomposing the product at high temperatures. Alloys containing more than 2% magnesium should not be used if water is present.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (750 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Protect cylinders from physical damage.

Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125 °F (52 °C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. For additional handling recommendations, consult Compressed Gas Association Pamphlet P-1. Handle with reasonable care. Store in a cool, dry place.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

Section 8- Exposure Controls/Personal Protection

**EXPOSURE LIMITS<sup>1</sup>:**

INGREDIENT	%VOLUME	PEL-OSHA <sup>2</sup>	TLV-ACGIH <sup>3</sup>	LD <sub>50</sub> or LC <sub>50</sub> Route/Species
Hexafluoroethane Formula: C <sub>2</sub> F <sub>6</sub> CAS: 76-16-4 RTECS#: KI4110000	99.9	Not Available	Not Available	LC <sub>50</sub> >200,000 ppm/2hr (rat)

<sup>1</sup> Refer to individual state of provincial regulations, as applicable, for limits which may be more stringent than those listed here.

<sup>2</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

<sup>3</sup> As stated in the ACGIH 1994-1995 Threshold Limit Values for Chemical Substances and Physical Agents.

**ENGINEERING CONTROLS:**

Hood with forced ventilation; provide local exhaust to prevent accumulation above the exposure limit.

**EYE/FACE PROTECTION:**

Not needed as product is a gas at room temperatures.

**SKIN PROTECTION:**

Any BUT natural rubber.

**RESPIRATORY PROTECTION:**

A Type C respirator with full-face piece equipped with an escape bottle or a self-contained breathing apparatus should be available for emergency use. Operate this equipment in the positive pressure demand mode.

**OTHER/GENERAL PROTECTION:**

Safety shoes, eyewash "fountain."

**Section 9- Physical and Chemical Properties**

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure at 70 °F	: 445	psia
Vapor density at 70 °F (Air = 1)	: 4.78	
Evaporation point	: Not Available	
Boiling point	: -108.8	°F
	: -78.2	°C
Freezing point	: -149.3	°F
	: -100.7	°C
pH	: Not Applicable	
Specific gravity	: Not Applicable	
Oil/water partition coefficient	: Not Available	
Solubility (H <sub>2</sub> O)	: Very low solubility	
Odor threshold	: Not Available	
Odor and appearance	: An odorless, colorless gas shipped in high pressure cylinders.	

**Section 10- Stability and Reactivity**
**STABILITY:**

Stable

**INCOMPATIBLE MATERIALS:**

May react violently with chemically active metals such as sodium, potassium and barium, powdered magnesium, powdered aluminum and organometallics.



## HAZARDOUS DECOMPOSITION PRODUCTS:

Decomposes at fire temperatures to hydrofluoric acid and carbonyl fluoride.

## HAZARDOUS POLYMERIZATION:

Will not occur.

### Section 11- Toxicological Information

No chronic effects data given in the Registry of Toxic Effects of Chemical Substances (RTECS) or Sax, Dangerous Properties of Industrial Materials, 7th ed.

### Section 12- Ecological Information

No data given.

### Section 13- Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Hynote or authorized distributor for proper disposal.

### Section 14- Transport Information

DOT/IMO SHIPPING NAME: Hexafluoroethane (R116)

HAZARD CLASS: 2.2

IDENTIFICATION NUMBER: UN 2193

PRODUCT RQ: None

SHIPPING LABEL(s): NONFLAMMABLE GAS

PLACARD (when required): NONFLAMMABLE GAS

### Section 15- Regulatory Information

SARA TITLE III NOTIFICATIONS AND INFORMATION

SARA TITLE III - HAZARD CLASSES:

Acute Health Hazard

Sudden release of Pressure Hazard

### Section 16- Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose.

NOTICE TO READER

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, SHANGHAI HYNOTE MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY SHANGHAI HYNOTE OR OTHERS IS TO BE INFERRED.

THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT SHANGHAI HYNOTE FOR THE MOST CURRENT VERSION OF THIS MSDS. SHANGHAI HYNOTE DOES NOT ASSUME RESPONSIBILITY FOR MSDS OBTAINED FROM THIRD PARTY SOURCES. UNLESS SPECIFICALLY AGREED OTHERWISE, SHANGHAI HYNOTE DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL, OF THE PRODUCTS DESCRIBED HEREIN.